

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: Mircea Gradu

GROUP:

SERIAL NO.:

EXAMINER:

FILED: December 9, 2003

DOCKET NO.: TIMK 8823US

FOR: STABILIZER BAR HAVING VARIABLE TORSIONAL STIFFNESS

St. Louis, Missouri
December 9, 2003

Mail Stop PATENT APPLICATION
Commissioner for Patents
PO Box 1450
Alexandria, VA 22313-1450

INFORMATION DISCLOSURE STATEMENT
PURSUANT TO §1.97 AND § 1.98

Sir:


The information, patents and/or literature references listed on the attached form PTO-1449, copies of which are enclosed, are being submitted within three months of the filing date of a national application other than a continued prosecution application under § 1.53(d); within three months of the date of entry of the national stage as set forth in § 1.491 in an international application; before the mailing of a first Office action on the merits; or before the mailing of a first Office Action after the filing of a request for continued examination under § 1.114. **Therefore, no fee is due.**

TIMK 8823US

Express Mail No. EV 255300739 US

The Commissioner is hereby authorized to charge any additional fees or credit overpayment under 37 CFR 1.16 and 1.17 which may be required by this paper to Deposit Account 162201. *Duplicate copies of this sheet are enclosed.*

Respectfully submitted,




Date: December 9, 2003

Edward A. Boeschstein,
Registration No. 22,986
POLSTER, LIEDER, WOODRUFF
& LUCCHESI, L.C.
763 South New Ballas Road
St. Louis, MO 63141
(314) 872-8118
(314) 991-2178 (fax)

Certificate of Mailing

I hereby certify that this correspondence is being deposited with the United States Postal Service utilizing the "Express Mail Post Office to Addressee" service addressed to Mail Stop Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on December 9, 2003.



Edward A. Boeschstein, Reg. No. 22,986
Express Mail No. EV 255300739 US

TIMK 8823US
Express Mail No. EV 255300739 US

FORM PTO-1449 U.S. DEPARTMENT OF COMMERCE, PATENT AND TRADEMARK OFFICE INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Use several sheets if necessary)	ATTY. DOCKET NO.: TIMK 8823US	SERIAL NO.:
	APPLICANT: MIRCEA GRADU	
	Filing Date: 12/09/03	Group:

U.S. PATENT DOCUMENTS

Examiner Initial	Document Number										Kind Code (click here)	Patent Issue Date OR US App. Pub. Date OR US Non-Published Application Filing Date	Name
	US	5	8	2	6	6	8	7				10/27/1998	Büngeler et al.
	US	5	8	4	5	7	5	3				12/08/1998	Bansbach
	US	6	4	2	8	0	1	9				08/06/2002	Kincad et al.
	US	6	5	0	7	7	7	8				01/14/2003	Koh
	US	6	2	4	1	0	6	7				06/05/2001	Höck

FOREIGN PATENT DOCUMENTS

Examine r Initial	Document Number								Date	Country	Translation	
											Yes	No
	GB	2	2	3	0	2	3	7 A	10/17/1990	United Kingdom		
	DE	4	4	4	3	8	0	9 A1	04/04/1996	Germany	X	

OTHER DOCUMENTS (Including Author, Title, Date, Pertinent Pages, Etc.)

		Brochure, DELPHI Energy & Chassis Sysems, 2002, "Dynamic Body Control System"
		Brochure, SAE International, Aleksander Hac, March 2002, "Influence of Active Chassis Systems on Vehicle Propensity to Maneuver-Induced Rollovers"

EXAMINER	DATE CONSIDERED
-----------------	------------------------

EXAMINER: Initial if citation considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

(Form PTO-1449)

TIMK 8823US

Express Mail No. EV 255300739 US

**CONCISE EXPLANATION OF RELEVANCE
of Offenlegungsschrift
DE 44 43 809 A1**

Referring to Figs. 1 and 2, a stabilizer 21, 23 for the front suspension system of an automotive vehicle has a stabilizer unit 19 that includes a housing 47 and a rotor 49 located within the housing 47. The rotor 49 has vanes 51 which project outwardly toward the inside surface of the housing 47, and the housing 47 has vanes 53 which project inwardly toward the rotor 49. The vanes 51 lie between the vanes 53 and vice versa, and the alternating vanes 51 and 53 create spaces 55 within the housing 47. The space 55 contain a hydraulic fluid, the pressure of which is controlled through a hydraulic line 57. The pressure of the fluid in the spaces 55 controls the stiffness of the stabilizer 21, 23 – the greater the pressure, the greater the stiffness.